


Date of Deposit 20-Aug-2001

Express Mail Label No. EL541370154US

Signature



Name

Brenda D. Chambers

DP-305008

PATENT

EVAPORATIVE SOLENOID CONTROL VALVE WITH ENHANCED DURABILITY FEATURES

TECHNICAL FIELD

[0001]

The present invention relates to control valves and in particular, to an evaporative (EVAP) solenoid control valve having enhanced durability and noise reduction features.

BACKGROUND OF THE INVENTION

[0002]

It is known in the art of automotive fuel systems to use an evaporative (EVAP) solenoid valve assembly to control the flow of fuel vapor through passageways connecting a purge canister and an intake manifold. One such EVAP control valve assembly includes a solenoid assembly actuated in response to a pulse width modulated (PWM) signal generated by the vehicle's central computer to induce a rubber-tipped plunger to move toward a metal stop, opening a passageway to the flow of vapor. When the solenoid is de-energized, the plunger is pushed back toward a valve seat by a pre-loaded spring situated between the stop and the plunger, causing the rubber-tip of the plunger to seal the passageway.

[0003]

To reduce the noise caused by the impact of the plunger against the metal valve stop, EVAP control valve plungers have been designed to include a soft, rubber-like stop cushion at the interface with the valve stop. Repeated impact with the metal valve stop, however, may cause deterioration of the stop cushion which may, in turn, contribute to additional noise. Moreover, such cushions, generally injection molded onto a metal preform plunger body, may be formed with a dimple at or near the cushion-stop impact surface.

SUMMARY OF THE INVENTION

[0004]

The present invention provides an improved evaporative control valve with enhanced durability and noise reduction features. In general, the control valve includes a valve body defining an inlet, a controlled outlet and a passageway therebetween. A valve stop and a valve seat are supported within the valve body in axial alignment with the controlled outlet. A plunger is reciprocally moveable between the valve stop and the valve seat to open and close the controlled outlet and further includes a central bore having an insert molded therein to define a stop-cushion at an end proximal the valve stop and a valve tip at an end proximal the valve seat. Connecting the stop cushion with the valve tip allows the cushion to be molded through the body of the plunger so that injection molding equipment interfaces with a non-impact surface of the insert (e.g. the side of the valve tip), and does not disturb the cushion-stop impact surface.

[0005]

According to another aspect of the invention, the stop cushion may be dome-shaped to provide a greater quantity of material for enhanced impact absorption and to increase the size of the stop-impact surface. This results in less stress and wear on the assembly components.

[0006]

Another aspect of the invention provides for a valve stop including a non-conducting surface, which may take the form of a plastic insert, that improves the path of the magnetic flux and reduces noise created by the impact of the plunger against the stop.

[0007]

Yet another aspect of the invention includes placement of the spring within a plunger pocket formed in the end of the plunger proximal the valve stop to improve spring force distribution and plunger-to-valve seat alignment.

[0008]

The above-described and other features and advantages of the present invention will be appreciated and understood by those skilled in the art from the following detailed description, drawings and appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

- [0009] The description herein makes reference to the accompanying drawings wherein like reference numerals refer to like parts throughout the several views, and wherein:
- [0010] Figure 1 is a schematic view of an EVAP valve within a fuel system;
- [0011] Figure 2 is a cross-sectional view of an EVAP valve embodying all of the inventive aspects summarized above; and
- [0012] Figure 3 is an enlarged cross-sectional view of a portion of the EVAP valve of Figure 2.

DESCRIPTION OF THE PREFERRED EMBODIMENT

- [0013] As shown in Figure 1, an EVAP valve assembly 10 is operatively connected within a fuel system to control the flow of vapor between a filtration canister 12 and an intake manifold 14. Figures 2 and 3 illustrate in detail the valve assembly 10 which includes a valve body 16 that defines a vapor flow path from an inlet 18, connectable to the filtration canister, through a cross-passageway 20 to a lower chamber 22 formed between a valve body end cap 24 and an end plate 26. The valve body end cap 24 defines a controlled outlet 28 that extends into the lower chamber 22, and which is connectable to the intake manifold. Controlled outlet 28 is aligned on a vertical axis 30. At the interface of the lower chamber 22 and outlet 28 and in axial alignment therewith is a valve seat 32 used in opening and closing the outlet 28.
- [0014] The valve body 16 further includes a central cavity 34 that houses a solenoid assembly 36. The solenoid assembly 36 includes a coil 38 wound about a spool 40 to define a central bore 42 on axis 30. The solenoid assembly 36 and a bearing 44 are supported within central cavity 34 and central bore 42 respectively, between end plate 26 and plate 45.
- [0015] Bearing 44 further supports a valve stop 46 and a plunger 48, in axial alignment with the valve seat 32 and controlled outlet 28. In a preferred embodiment, the bearing 44 is preferably made of a polished material to

minimize friction between the components.

[0016]

The plunger 48 has a body 50 made from a conductive material, and is preferably a steel preform. The stop 46, likewise, has a conductive body 52 preferably made from steel. An air gap 54 separates the conductive stop body 52 and plunger body 50, creating a path for magnetic flux travel when the solenoid assembly 36 is energized. In this embodiment, the solenoid assembly 36 is energized by a pulse width modulated (PWM) signal generated by the vehicle's central computer (not shown).

[0017]

The conductive body 52 of valve stop 46 is adapted to receive a non-conductive insert 56 (preferably plastic) that is press fit into a bore 58 formed in an end 60 of the conductive stop body 52 proximal the plunger 48 axially extending beyond the end 60 of the conductive stop body 52 along the axis 30. The insert 56 has a plunger-impact surface 62 at end 64. In its normally seated or closed position, shown in Figure 2, the plunger 48 is separated from the plunger-impact surface 62 by a gap 66 of predetermined size depending on the desired stroke of the solenoid assembly 36.

[0018]

The particular non-conductible stop insert 56 illustrated in Figures 2 and 3 has the added advantage of enhancing alignment on axis 30 between a spring 68 mounted about the insert 56 and received in a pocket 70 formed in an end 72 of the plunger body 50 proximal the valve stop 46. The pocket 70 is appropriately sized and shaped to create the desired gap 66 as well as to enclose the spring 68. To this end, the insert 56 is shown to include an annular shoulder 74 which retains the spring 68 against the compressive force of the plunger 48 as it moves toward the plunger-impact surface 62 of the valve stop 46. Normally, the spring 68 biases the plunger 48 to seat against the valve seat 32. The outer diameter of the spring 68 is at least 50% of the diameter of the pocket, making it easier to handle. As shown in Figure 2, the spring 68 is received between the base of pocket 78, and the annular shoulder 74 of the plastic insert 56.

[0019]

The plunger body 50 has a central bore 76 axially extending from the base 78 of the pocket 70 to the opposite end 80 along the axis of plunger

movement, in this case, axis 30. An insert 81 defining a valve tip 82 is formed on the end 80 of the plunger body 50 for sealing engagement with the valve seat 32 and is connected to a stop cushion 84 that protrudes through the pocket base 78 into the pocket 70 formed in the end 72 of the plunger 48 proximal the valve stop 46. This uniquely connected valve tip 82 and stop-cushion 84 permits both elements to be manufactured by a single shot injection molding process delivering material through the central bore 76 in the plunger body 50 (the preform) to the opposite end 80 of the plunger body 50. In this way, the injection molding equipment does not interface directly with the outer surface of the stop-cushion 84 in any way, therefore, eliminating the formation of dimples by supply gates or risers.

The particular stop cushion 84 shown in Figures 2 and 3 has a dome-shape which provides additional material to absorb the shock of impact with the plastic insert 56 of the valve stop 46 and a greater stop-impact surface 86 area for engaging the plunger impact surface 62 of the plastic insert 56 of the stop 46. Due to its unique shape, greater dampening material of the stop cushion 84 come into engagement with the plastic insert 56 of the stop 46 as the cushion 84 is compressed during impact. Stop cushion 84 may be made of rubber or a flouroelastomer.

In operation, the EVAP control valve assembly 10 may be installed as shown in Figure 1, between a filtration canister 12 and an intake manifold 14. As shown in Figure 2, vapor flows from the filtration canister, through inlet 18 and cross-passageway 20 into lower chamber 22, where the vapor will be retained until the plunger is moved from its normally seated position against valve seat 28 to open the controlled outlet leading to the intake manifold. In this embodiment, the solenoid assembly 36 operates in the plunger creating a magnetic force that pulls the plunger 48 toward the valve stop 46 where the plunger's dome-shaped stop cushion 84 impacts the plastic stop insert 56 and compress, to reduce the force of impact and any resulting noise. Since the insert 56 is preferably plastic, noise that may be created by the plunger 48 upon impact with the valve stop

A

1927-1928 1929-1930 1931-1932 1933-1934 1935-1936 1937-1938 1939-1940 1941-1942 1943-1944 1945-1946 1947-1948 1949-1950 1951-1952 1953-1954 1955-1956 1957-1958 1959-1960 1961-1962 1963-1964 1965-1966 1967-1968 1969-1970 1971-1972 1973-1974 1975-1976 1977-1978 1979-1980 1981-1982 1983-1984 1985-1986 1987-1988 1989-1990 1991-1992 1993-1994 1995-1996 1997-1998 1999-2000 2001-2002 2003-2004 2005-2006 2007-2008 2009-2010 2011-2012 2013-2014 2015-2016 2017-2018 2019-2020 2021-2022 2023-2024 2025-2026 2027-2028 2029-2030 2031-2032 2033-2034 2035-2036 2037-2038 2039-2040 2041-2042 2043-2044 2045-2046 2047-2048 2049-2050 2051-2052 2053-2054 2055-2056 2057-2058 2059-2060 2061-2062 2063-2064 2065-2066 2067-2068 2069-2070 2071-2072 2073-2074 2075-2076 2077-2078 2079-2080 2081-2082 2083-2084 2085-2086 2087-2088 2089-2090 2091-2092 2093-2094 2095-2096 2097-2098 2099-2100 2101-2102 2103-2104 2105-2106 2107-2108 2109-2110 2111-2112 2113-2114 2115-2116 2117-2118 2119-2120 2121-2122 2123-2124 2125-2126 2127-2128 2129-2130 2131-2132 2133-2134 2135-2136 2137-2138 2139-2140 2141-2142 2143-2144 2145-2146 2147-2148 2149-2150 2151-2152 2153-2154 2155-2156 2157-2158 2159-2160 2161-2162 2163-2164 2165-2166 2167-2168 2169-2170 2171-2172 2173-2174 2175-2176 2177-2178 2179-2180 2181-2182 2183-2184 2185-2186 2187-2188 2189-2190 2191-2192 2193-2194 2195-2196 2197-2198 2199-2200 2201-2202 2203-2204 2205-2206 2207-2208 2209-2210 2211-2212 2213-2214 2215-2216 2217-2218 2219-2220 2221-2222 2223-2224 2225-2226 2227-2228 2229-2230 2231-2232 2233-2234 2235-2236 2237-2238 2239-2240 2241-2242 2243-2244 2245-2246 2247-2248 2249-2250 2251-2252 2253-2254 2255-2256 2257-2258 2259-2260 2261-2262 2263-2264 2265-2266 2267-2268 2269-2270 2271-2272 2273-2274 2275-2276 2277-2278 2279-2280 2281-2282 2283-2284 2285-2286 2287-2288 2289-2290 2291-2292 2293-2294 2295-2296 2297-2298 2299-2300 2301-2302 2303-2304 2305-2306 2307-2308 2309-2310 2311-2312 2313-2314 2315-2316 2317-2318 2319-2320 2321-2322 2323-2324 2325-2326 2327-2328 2329-2330 2331-2332 2333-2334 2335-2336 2337-2338 2339-2340 2341-2342 2343-2344 2345-2346 2347-2348 2349-2350 2351-2352 2353-2354 2355-2356 2357-2358 2359-2360 2361-2362 2363-2364 2365-2366 2367-2368 2369-2370 2371-2372 2373-2374 2375-2376 2377-2378 2379-2380 2381-2382 2383-2384 2385-2386 2387-2388 2389-2390 2391-2392 2393-2394 2395-2396 2397-2398 2399-2400 2401-2402 2403-2404 2405-2406 2407-2408 2409-2410 2411-2412 2413-2414 2415-2416 2417-2418 2419-2420 2421-2422 2423-2424 2425-2426 2427-2428 2429-2430 2431-2432 2433-2434 2435-2436 2437-2438 2439-2440 2441-2442 2443-2444 2445-2446 2447-2448 2449-2450 2451-2452 2453-2454 2455-2456 2457-2458 2459-2460 2461-2462 2463-2464 2465-2466 2467-2468 2469-2470 2471-2472 2473-2474 2475-2476 2477-2478 2479-2480 2481-2482 2483-2484 2485-2486 2487-2488 2489-2490 2491-2492 2493-2494 2495-2496 2497-2498 2499-2500 2501-2502 2503-2504 2505-2506 2507-2508 2509-2510 2511-2512 2513-2514 2515-2516 2517-2518 2519-2520 2521-2522 2523-2524 2525-2526 2527-2528 2529-2530 2531-2532 2533-2534 2535-2536 2537-2538 2539-2540 2541-2542 2543-2544 2545-2546 2547-2548 2549-2550 2551-2552 2553-2554 2555-2556 2557-2558 2559-2560 2561-2562 2563-2564 2565-2566 2567-2568 2569-2570 2571-2572 2573-2574 2575-2576 2577-2578 2579-2580 2581-2582 2583-2584 2585-2586 2587-2588 2589-2590 2591-2592 2593-2594 2595-2596 2597-2598 2599-2600 2601-2602 2603-2604 2605-2606 2607-2608 2609-2610 2611-2612 2613-2614 2615-2616 2617-2618 2619-2620 2621-2622 2623-2624 2625-2626 2627-2628 2629-2630 2631-2632 2633-2634 2635-2636 2637-2638 2639-2640 2641-2642 2643-2644 2645-2646 2647-2648 2649-2650 2651-2652 2653-2654 2655-2656 2657-2658 2659-2660 2661-2662 2663-2664 2665-2666 2667-2668 2669-2670 2671-2672 2673-2674 2675-2676 2677-2678 2679-2680 2681-2682 2683-2684 2685-2686 2687-2688 2689-2690 2691-2692 2693-2694 2695-2696 2697-2698 2699-2700 2701-2702 2703-2704 2705-2706 2707-2708 2709-2710 2711-2712 2713-2714 2715-2716 2717-2718 2719-2720 2721-2722 2723-2724 2725-2726 2727-2728 2729-2730 2731-2732 2733-2734 2735-2736 2737-2738 2739-2740 2741-2742 2743-2744 2745

While the invention has been described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the scope of the invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiment disclosed as the best mode contemplated for carrying out this invention, but that the invention will include all embodiments falling within the scope of the appended claims. Accordingly, it is to be understood that the present invention has been described by way of illustration and not limitation.